

LP5 Plus Data Sheet

Functions

Lifting capacity	: 300 kg
Lifting speed	: 13 mm/sec
Operation	
Electric	: Operating panel
Emergency stop	: Electronic
Emergency lowering	: Mechanical
Safety lists	: Mechanical/electrical safety lists

Weight

LP5+	: 150 kg
Safety gate	: 76 kg

Materials

Materials	: Aluminium
Materials	: Powder coated/galvanized steel
Railing	: Aluminium and transparent polycarbonate
Safety gate	: Powder coated steel and hardened safety glass
Cover plate, Safety gate	: Electro-galvanized steel plate

Measurements

A	: 150 - 875 mm
B	: 1100 mm
C	: 1602 mm
D	: 790 mm
E	: 900 mm
F	: 1076 mm
Max. lifting height without safety gate	: 500 mm

Safety gate

G	: 945 mm
H	: 1100 mm
J	: 50 mm
K	: 1150 mm
L	: 120 mm

Electrical parts

On/off	: Automatically
Power consumption	
Stand-by	: 3 W
Operation	: 14,7 W
Periodic load	: 10/90
Fuse	: T10A
Batteries	: 2 x 12V/4.5 Ah Gastight and maintenance-free
Power supply	
Primary	: 230 V/115 V
Secondary	: 24 V DC

Classification, tightness

Components	: IP 65
Operating panel	: IP 67
Safety gate	
Components	: IP 65

Accessories/ Miscellaneous

: External control panel
: Wireless operation
: Safety gate
: Hand control with spiral cable
: Exit in right/left platform side

Marking

The product is manufactured in compliance with the Council Directive 2006/42/EC of May 17th 2006 on machinery and amending Directive 95/16/EC.

Item Number/Model

13056-101	: LP5+, standard
13056-102	: LP5+, for recessing
130590	: Safety gate, automatic, left-hinged (seen from the upper landing)
130595	: Safety gate, automatic, right-hinged (seen from the upper landing)

Classification

According to ISO 9999	: 18 30 06
-----------------------	------------

