

## Technical specifications

### Functions

Lifting capacity : 300 kg  
Lifting speed : 20-25 mm/sec

### Operation

Electric : Operating panel  
Emergency stop : Electronic  
Emergency lowering : Mechanical  
Safety lists : Mechanical/electrical safety lists

### Weight

: 149 kg

### Materials

Platform/Ramps : Aluminium  
Base frame : Steel, powder coated  
Railing : Aluminium, powder coated

### Measurements

A : 180 - 940 mm  
B : 1140 mm  
C : 850 mm  
D : 1200 mm  
E : 1400 mm  
F : 1630 mm

### Electrical parts

On/off : Automatically  
Power consumption  
Stand-by : 3 W  
Operation : 14,7 W  
Periodic load : 10/90  
Fuse : T10A  
Batteries : 2 x 12V/7,2 Ah  
Gastight and maintenance-free  
Power supply & charger  
Primary : 230 V/115 V  
Secondary : 24 V DC

### Classification, tightness

Components : IP 65  
Operating panel : IP 67

### Marking

CE-marked according to ISO/DIS 9386-1 : Power-operated lifting platforms for persons with impaired mobility  
EN 60601-1-2 : Medical electrical equipment  
98/37/EEC : Approximation of the laws of the Member States on the safety of machines

### Classification

according to ISO 9999 : 18 30 06

